



Artikel-Nr.: 4509
Hersteller: Kramer AV



EXT3-C-XR-T

€ 832,50 *

zzgl. MwSt. [zzgl. Versandkosten](#)
Lieferzeit ca. 5 Tage

Produktinformationen "EXT3-C-XR-T"

HDBaseT 3.0 Transmitter für 4K60 4:4:4 USB-C DP alt-mode, USB, Ethernet, RS-232, und IR, mit eXtra Reichweite

- High Performance Standard Extender Professional HDBaseT extender for providing extended-reach signals over twisted-pair copper infrastructures. EXT3-C-XR-T is a standard extender that can be connected to any market-available HDBaseT-compliant extension product. For optimum extension reach and performance, use recommended Kramer cables.
- BYOD Ease and Convenience Connect any DP-Alt-Mode-capable USB-C device as an AV presentation source, while providing the connected device with USB 2.0 and Ethernet connection, and (if PD-2.0-capable) up to 60 watts of power, via a single USB-C cable connection only.
- Convenient Display Power On/Off Control Simply press the DISPLAY ON button to toggle on and off the power of the remote CEC-enabled display; button LED indicates the power on/off status of the remote display.
- HDMI Signal Extension Uncompressed 4K@60Hz (4:4:4) HDMI, HDCP 2.3, EDID and CEC signals are passed through from the source to the display.
- HDMI Support Supports HDR10, deep color, x.v.Color™, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0.
- HDMI Mirroring Transmitter mirrors input HDMI signal to loop output port for connecting a local monitor or adding an additional unit in a daisy chain.
- Flexible USB 2.0 Extension An active USB host is connected to the extender at either the transmitter or receiver sides. USB 2.0 signals are extended between the extender transmitter and receiver sides, enabling connection of the active USB host to both local and remote USB devices, such as camera and audio devices, or HID (Human Interface Devices) mouse or keyboard devices.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ Intelligent EDID handling, processing, and pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems.
- Multi-channel Audio Transmission Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound.
- Ethernet Extension Ethernet interface data flows in both directions allowing extension of up to 1 Gbps Ethernet connectivity for LAN communication and device control.
- Bidirectional RS-232 Extension Serial interface data flows in both directions allowing data transmission and device control.
- Bidirectional Infrared Extension IR interface data flows in both directions allowing remote control of peripheral devices located at either end of the extended line.
- Cost-effective Maintenance Status LED indicators for HDMI, Loop, HDBT, and USB active host ports, facilitate easy local maintenance and troubleshooting.
- Easy and Elegant Installation MegaTOOLS™ fan-less enclosure for dropped-ceiling mounting, or side-by-side mounting of 2 units in a 1U rack space with the recommended rack adapter.
- Produktabmessung: 19.00cm x 11.60cm x 2.70cm (7.48 x 4.57 x 1.06) W, D, H
- Versandabmessung: 34.50cm x 21.00cm x 6.70cm (13.58 x 8.27 x 2.64) W, D, H
- Produktgewicht: 0.6kg (1.2lbs) approx.
- Versandgewicht: 1.2kg (2.5lbs) approx.

Gebrauchsanleitung:

[Gebrauchsanleitung EXT3-C-XR-T](#)

Weiterführende Links zu"EXT3-C-XR-T"

- [- Fragen zum Artikel?](#)
- [- Weitere Artikel von Kramer AV](#)

Demo GmbH
Steuer-Nr
UST-ID:
Finanzamt Musterstadt

Bankverbindung
Sparkasse Musterstadt
BLZ:
Konto:
aaaa

AGB
Gerichtsstand ist Musterstadt
Erfüllungsort Musterstadt
Gelieferte Ware bleibt bis zur vollständigen
Bezahlung unser Eigentum

Geschäftsführer
Max Mustermann