




Artikel-Nr.: 4589
Hersteller: Kramer AV



M4250-40G8F-PoE+

€ 832,50 *

zzgl. MwSt. [zzgl. Versandkosten](#)
Lieferzeit ca. 5 Tage

Produktinformationen "M4250-40G8F-PoE+"

- The NETGEAR M4250 series ranges from 8 to 48 ports with a variety of PoE+ and Ultra90 PoE++ options for 15.4W, 30W, 60W, 75W and 90W AVoIP endpoints.
- Uplink options include 1G for audio installations or standalone video installations as well as 10G uplinks for larger scale video deployments.
- Also includes 12-port multi-gigabit Ethernet and 16-port 1G/10G fiber models for plug and play aggregation in a star topology.
- Designed for a clean integration with traditional, rack-mounted, AV equipment.
- A second pair of rackmount ears allows the switches to be mounted recessed by 2-inches to allow for the cabling.
- Threaded holes on the bottom (4xM5 for 50x100mm VESA) and in front (1xM10 for clamps) allow for universal mounting options outside the rack as well.
- For audio, profiles for Dante, Q-SYS and AES67 are built-in, as well as an AVB profile (AVB license sold separately).
- To further simplify star deployments, NETGEAR IGMP Plus™ brings multicast automation between all M4250 switches, and with M4300/M4500.
- Auto-Trunk and Auto-LAG simply connect M4250 switches together.
- All M4250 switches share the same high-end NETGEAR Layer 2 / Layer 3 switching engine for a consistent experience.
- All switches in the M4250 series have another main, IT web-based GUI for midsize Enterprise campus networks, IoT and IPTV.
- Additional features include static, RIP and PIM-SM, DM and SSM multicast routing, DHCP Server and PTPv2 Transparent Clock (1-step E2E).
- Efficient authentication tiering with successive DOT1X, MAB and Captive Portal methods for streamlined BYOD.
- Comprehensive IPv4/IPv6 static and dynamic routing including Policy-based routing and 6-to-4 tunneling.
- Advanced IPv4/IPv6 security implementation including malicious code detection, DHCP Snooping, IP Source Guard protection and DoS attacks mitigation.
- Produktabmessung: 44.00cm x 40.00cm x 4.32cm (17.32 x 15.75 x 1.70) W, D, H
- Versandabmessung: 53.60cm x 46.60cm x 12.20cm (21.10 x 18.35 x 4.80) W, D, H
- Produktgewicht: 5.9kg (12.9lbs) approx.
- Versandgewicht: 7.9kg (17.4lbs) approx.

Weiterführende Links zu "M4250-40G8F-PoE+"

- - [Fragen zum Artikel?](#)
- - [Weitere Artikel von Kramer AV](#)