



Artikel-Nr.: 4470
Hersteller: Kramer AV

DTAxrD2P-OUT2-F34

€ 832,50 *

zzgl. MwSt. [zzgl. Versandkosten](#)
Lieferzeit ca. 5 Tage

Produktinformationen "DTAxrD2P-OUT2-F34"

2-Channel 4K HDR HDMI over HDBaseT 2.0 DSC Output Card with Analog Audio & PoE Provider

- Max. Data Rate 18Gbps (6Gbps per graphics channel), 10Gbps DSC over CAT cable.
- Max. Resolution 4K@60Hz (4:4:4).
- PoE Provider Provides power over Ethernet to connected devices.
- Analog Audio Embedding/De-embedding or ARC On the same jack.
- HDBaseT Technology HDTV compatible, HDCP 2.2/1.4 compliant.
- System Range Up to 100m at normal mode (4K), up to 130m (430ft) at normal mode (2K), up to 180m (590ft) ultra mode (1080p @60Hz @24bpp). Note: When using Kramer HDBaseT cables.
- Ethernet Extension Ethernet interface data flows in both directions, allowing extension of up to 100Mbps Ethernet connectivity for LAN communication and device control.
- Bidirectional RS-232 Extension: Serial interface data flows in both directions, allowing data transmission and device control.
- Bidirectional Infrared Extension: IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line.
- 3D Pass-Through.
- PoE (Power over Ethernet) Enabled Provides PoE power to a connected device with the Kramer PoE Power Supply Add-On PS-4812 (sold separately).
- Produktabmessung: 25.00cm x 13.00cm x 2.00cm (9.84 x 5.12 x 0.79) W, D, H
- Versandabmessung: 29.30cm x 16.50cm x 5.90cm (11.54 x 6.50 x 2.32) W, D, H
- Produktgewicht: 0.3kg (0.7lbs) approx.
- Versandgewicht: 0.5kg (1.0lbs) approx.

Gebrauchsanleitung:

[Gebrauchsanleitung DTAxrD2P-OUT2-F34](#)

Weiterführende Links zu "DTAxrD2P-OUT2-F34"

- [- Fragen zum Artikel?](#)
- [- Weitere Artikel von Kramer AV](#)