



Artikel-Nr.: 4686  
Hersteller: Kramer AV

## MC3-2Ri

**€ 832,50 \***

zzgl. MwSt. [zzgl. Versandkosten](#)  
Lieferzeit ca. 5 Tage

### Produktinformationen "MC3-2Ri"

2-Kanal 4K60 HDBT Eingangskarte mit eXtra Reichweite

- High Performance Standard Extender Professional HDBaseT extender for providing long-reach signals over twisted-pair copper infrastructures. It employs low-level video compression technology that delivers visually lossless performance for 4K@60 (4:4:4) and HDR signals with near-zero latency. This high-quality compressed signal is extended to almost double the extension reach of the uncompressed signal
- Future-proof, Standard Extender Matrix card is a standard HDBaseT extender, backwards compatible with other standard HDBT extenders. It extends either compressed or uncompressed HDBaseT signal, by auto-adapting to the compression capabilities of its connected extender. This enables it to be connected to any market-available HDBaseT-compliant extension product.
- Intelligent Compression Handling Automatically detects a standard HDBaseT extender without compression and disables the compression to extend the signal in compliance with the detected extender.
- HDMI™ Signal Distribution HDCP 2.2 compliant, supporting deep color, x.v.Color™, CEC, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified by the HDMI 2.0 standard.
- Multi-channel Audio Transmission Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound.
- Ethernet Extension Ethernet interface data flows in both directions, allowing extension of up to 100Mbps Ethernet connectivity for LAN communication and device control.
- Intelligent Forward Audio Routing Per user selection independently per port, the analog audio port input signal is converted into a digital signal and embedded into the transmitted HDMI signal, or the embedded audio of the HDMI over HDBT input signal is de-embedded and output to the analog audio port. This enables temporarily overriding the audio with another audio source such as from a microphone, or playing the transmitted audio on high-quality external speakers.
- Intelligent ARC (Audio Return Channel) Routing The outputReturned ARC signal, per user selection independently per port, is routed to the analog audio bidirectional port that is associated with the HDBT input port. This enables playing the ARC audio on high-quality external speakers, and controlling its volume using an IR remote control either via a remote AV acceptor device (such as a display) or via a local AV acceptor device (such as an AV Receiver with speakers).
- Bidirectional RS-232 Extension Serial interface data flows in both directions, allowing data transmission and device control.
- Bidirectional Infrared Extension IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line.
- Easy Installation Supports PoE (Power over Ethernet) providing over HDBT cable, in parallel to signals extension, to a remote PoE acceptor such as a PoE wall-plate, when matrix is connected to PoE power supply module.
- Produktabmessung: 25.00cm x 13.00cm x 2.00cm (9.84 x 5.12 x 0.79 ) W, D, H
- Versandabmessung: 29.20cm x 16.50cm x 6.00cm (11.50 x 6.50 x 2.36 ) W, D, H
- Produktgewicht: 0.3kg (0.7lbs) approx.
- Versandgewicht: 0.5kg (1.1lbs) approx.

Gebrauchsanleitung:

[Gebrauchsanleitung MC3-2Ri](#)

### Weiterführende Links zu "MC3-2Ri"

- [- Fragen zum Artikel?](#)
- [- Weitere Artikel von Kramer AV](#)