



Artikel-Nr.: 4702
Hersteller: Kramer AV

SWT3-41-U

€ 832,50 *

zzgl. MwSt. [zzgl. Versandkosten](#)
Lieferzeit ca. 5 Tage

Produktinformationen "SWT3-41-U"

4x1 USB Switcher

- Collaborative Online-meeting Switching Controllable switching of online-session USB host participants and space-deployed visual (such as camera) and audible (such as microphones or headsets) USB peripherals, allows collaborative online meeting and smooth content sharing operation among online meetings participants.
- BYOD Ease and Convenience: Connect any USB-C device as an online meeting participant, while providing the connected device with multiple concurrent capabilities of USB 3.1 and Ethernet connection, USB-driven content sharing, and (if PD-2.0-capable) up to 60 watts of power, all via a single USB-C cable connection only.
- USB 3.2 Switching: USB 3.2 signals switching, enables high data-rate connection between active USB host and space USB devices, such as 4K camera, high-quality audio devices, and HID (Human Interface Devices) mouse or keyboard devices.
- Auto Switcher Ease of Use: Automatically connects the plugged host to the space connected USB peripherals, according to user-configured preferences, such as last-connected host.
- Simple and Flexible Control Remote IP-controller connection, browser operation webpage, local panel buttons, and remotely connected contact-closure buttons triggering configurable operation functions, for easy and fully flexible USB host ports selection, and switcher control.
- Built-in Intelligent Control Gateway Remote IP-driven intelligent control of connected USB and sensor devices via RS-232 or I/O. Eliminating the need for an external control gateway, this feature reduces installation complexity and costs, to enable easy integration with control systems, such as Kramer Control.
- Secured Operation: Standard IT-grade 802.1x authentication for secured IT LAN connectivity operation.
- Comprehensive and Cost-effective Management Local panel indication LEDs to facilitate easy local maintenance and troubleshooting. Remote IP-driven device firmware upgrade and management, via user-friendly embedded web pages and optional whole site management system, ensure lasting and field proven deployment.
- Easy and Elegant Installation: PoE powering via LAN port connection, and MegaTOOLS™ fan-less enclosure for desktop, under table or dropped-ceiling mounting, or side-by-side mounting of 2 units in a 1U rack space with the recommended rack adapter, for easy switcher deployment.
- Produktabmessung: 19.00cm x 19.50cm x 2.70cm (7.48 x 7.68 x 1.06) W, D, H
- Versandabmessung: 35.10cm x 21.20cm x 7.20cm (13.82 x 8.35 x 2.83) W, D, H
- Produktgewicht: 0.9kg (2.0lbs) approx.
- Versandgewicht: 1.5kg (3.2lbs) approx.

Gebrauchsanleitung:

[Gebrauchsanleitung SWT3-41-U](#)

Weiterführende Links zu "SWT3-41-U"

- [- Fragen zum Artikel?](#)
- [- Weitere Artikel von Kramer AV](#)