



Artikel-Nr.: 4720  
Hersteller: Kramer AV

## SWT3-21-H

€ 832,50 \*

zzgl. MwSt. [zzgl. Versandkosten](#)  
Lieferzeit ca. 5 Tage

### Produktinformationen "SWT3-21-H"

#### 2x1 4K60 HDMI Switcher

- Auto Switcher Ease of Use Automatically plays the switched source signal on the connected display according to user-configured preferences, such as priority or last-connected input. When the user manually switches, by pressing a button, the auto switching is overridden.
- HDMI Signal Switching HDCP 2.2 compliant, supporting deep color, x.v.Color™, CEC, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ Intelligent EDID handling, processing, locking and pass-through algorithm ensures plug & play operation for HDMI source and display systems
- Multi-channel Audio Switching Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound.
- Audio De-embedding The digital audio signal passing-through to the HDMI output, is de-embedded, converted to an analog signal and sent to the stereo balanced analog audio output. This enables playing the audio on a locally connected professional audio system (such as DSP) and speakers, in parallel to playing it on the speakers connected to the AV acceptor device (such as TVs with speakers).
- Display On/Off Operation Meeting presentation is simplified by manually or automatically turning ON/OFF a CEC-enabled or serially-controlled display when the presentation source is plugged in / unplugged with user-defined shut-down delay.
- Simple and Flexible Control Remote IP-controller connection, browser operation webpage, local panel buttons, and remotely connected contact-closure buttons triggering configurable operation functions, for easy and fully flexible user ports selection, signals routing, and switcher control.
- Built-in Intelligent Control Gateway Remote IP-driven intelligent control of connected HDMI and sensor devices via RS-232 or I/O. Eliminating the need for an external control gateway, this feature reduces installation complexity and costs, to enable easy integration with control systems, such as Kramer Control.
- Secured Operation Standard IT-grade 802.1x authentication for secured IT LAN connectivity operation.
- Comprehensive and Cost-effective Management Local panel indication LEDs to facilitate easy local maintenance and troubleshooting. Remote IP-driven device firmware upgrade and management, via user-friendly embedded web pages and optional whole site management system, ensure lasting and field proven deployment.
- Easy and Elegant Installation PoE powering via LAN port connection, and compact DemiTOOLS® fan-less enclosure for user-reachable table mounting, under table, dropped-ceiling mounting, or side-by-side mounting of 2 units in a 1U rack space with the recommended rack adapter, for easy switcher deployment.
- Produktabmessung: 19.05cm x 5.96cm x 2.74cm (7.50 x 2.35 x 1.08 ) W, D, H
- Versandabmessung: 34.50cm x 16.50cm x 5.20cm (13.58 x 6.50 x 2.05 ) W, D, H
- Produktgewicht: 0.3kg (0.7lbs) approx.
- Versandgewicht: 0.8kg (1.7lbs) approx.

#### Gebrauchsanleitung:

[Gebrauchsanleitung SWT3-21-H](#)

### Weiterführende Links zu "SWT3-21-H"

- - [Fragen zum Artikel?](#)
- - [Weitere Artikel von Kramer AV](#)

Demo GmbH  
Steuer-Nr  
UST-ID:  
Finanzamt Musterstadt

Bankverbindung  
Sparkasse Musterstadt  
BLZ:  
Konto:  
aaaa

AGB  
Gerichtsstand ist Musterstadt  
Erfüllungsort Musterstadt  
Gelieferte Ware bleibt bis zur vollständigen  
Bezahlung unser Eigentum

Geschäftsführer  
Max Mustermann