



Artikel-Nr.: 3132
Hersteller: Kramer AV

VM-214DT

€ 832,50 *

zzgl. MwSt. [zzgl. Versandkosten](#)
Lieferzeit ca. 5 Tage

Produktinformationen "VM-214DT"

2x1:4 4K (4:2:0) UHD HDMI und HDBaseT Verteilverstärker mit Ethernet, RS-232, IR und Audio

- High Performance Extender Distributor High-quality professional 1:4 distribution of native extended-reach HDBaseT signals, for deploying mid-way between an AV source and multiple remote displays and gaining extra extended-reach extension. It is coupled with both sides, input and output, extension of a maximum 4K@60Hz (4:2:0) 24bpp video resolution signal to maximum 100m (330ft) extended-reach over CAT copper cable, and even further reach for lower HD video resolution. The extender distributor is standard and capable of being connected to any market-available HDBaseT compliant extending product.
- Cables For optimum range and performance, use recommended Kramer cables.
- HDMI Signal Extension HDCP 1.4 compliant signal, supporting deep color, x.v.Color™, lip sync, 7.1 PCM, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0. EDID signals are passed through from the source to the display.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ An intelligent EDID handling, processing and pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems.
- Looping HDMI Output Enables monitoring and cascading to additional DAs.
- Ethernet Extension Ethernet interface data flows in both directions, enabling extension of up to 100Mbps Ethernet connectivity for LAN communication and control of devices.
- Bidirectional RS-232 Extension Serial interface data flows in both directions, enabling data transmission and control of devices.
- Bidirectional Infrared Extension IR interface data flows in both directions, enabling remote control of peripheral devices located at either end of the extended line.
- Cost-effective Maintenance Status LED indicators for HDMI and HDBT ports to facilitate easy local maintenance and troubleshooting.
- Remote IP device management via built-in web pages or RS-232 control connection. Local and remote firmware upgrade via mini-USB, control RS-232 or Ethernet connection and the K-Upload tool to ensure long field-proven deployment.
- Easy Installation Twisted-pair cables for HDBaseT signals wiring. Rack mountable enclosure for mounting in a 1U rack space with included rack ears.
- Produktabmessung: 43.64cm x 18.30cm x 4.36cm (17.18 x 7.20 x 1.72) W, D, H
- Versandabmessung: 55.00cm x 27.60cm x 10.70cm (21.65 x 10.87 x 4.21) W, D, H
- Produktgewicht: 1.6kg (3.4lbs) approx.
- Versandgewicht: 2.7kg (6.0lbs) approx.

Gebrauchsanleitung:

[Gebrauchsanleitung VM-214DT](#)

Weiterführende Links zu "VM-214DT"

- [- Fragen zum Artikel?](#)
- [- Weitere Artikel von Kramer AV](#)